



Cardinal Scale
model HSDC-500
digital hanging scale
with pushbutton tare

HSDC Series

Digital Hanging Scales



LEGAL FOR TRADE

Class III certificate
All HSDC models are NTEP
except model HSDC-500



Stainless Steel Eyehook
and Hook Included for
Versatile Weighing Use

- 1-inch-High Bold LCD Readouts for Easy Visibility
- Aluminum Alloy Enclosure for Lightweight Strength
- Up to 500-lb and 100-kg Capacities Available
- 9 Different Models to Select From
- Battery Powered for Convenient Portable Weighing

Cardinal Scale's HSDC Series Digital Hanging Scales

Fishing • Curbside Recycling Collection • Butchery/Meat Processing • Industrial Applications • Supermarkets



Powered by 6 C batteries for completely portable weighing (not included)
Auto Shutoff and Sleep Mode extend battery life



1-inch/25-mm-high bold LCD display
Lightning-fast and accurate digital readouts

Model HSDC-20KGP includes stainless steel bowl
Stainless steel bowl measures 13.7 in diameter x 4.4 in H / 34.8 cm diameter x 11.2 cm H



HSDC-20	HSDC-40	HSDC-100	HSDC-200	HSDC-500	HSDC-20KG/ HSDC-20KGP	HSDC-40KG	HSDC-100KG
20 lb x .01 lb	40 lb x .02 lb	99.95 lb x .05 lb	200 lb x .1 lb	500 lb x .2 lb	20 kg x .01 kg HSDC-20KGP features stainless steel pan	40 kg x .02 kg	99.95 kg x .05 kg
Scale Dimensions		Width: 8.5 in / 21.6 cm Depth: 5.1 in / 13.0 cm Height: 4.3 in / 10.9 cm					
Overall Dimensions (with hooks)		Width: 8.5 in / 21.6 cm Depth: 5.1 in / 13.0 cm Height: 14.0 in / 35.6 cm (including eyehook and hook)					
LCD Display Dimensions		Width: 3.3 in / 8.4 cm Height: 1.1 in / 2.8 cm					
LCD Digit Size		Width: 0.5 in / 1.3 cm Height: 1.0 in / 2.5 cm					
Product Weight		5.8 lb / 2.6 kg (10 lb / 4.5 kg with model HSDC-20KGP's stainless steel bowl and hanging assembly)					
Shipping Weight		7.2 lb / 3.3 kg (including packaging)					
Power		6 C size alkaline batteries (not included)					
Operating Temperature		+14° to 104°F (-10° to +40°C)					
Zero		Established during setup and maintained automatically to ± 1/4 graduation					
Auto Zero Range		5 and 0 through 9 graduations					
Calibration Method		Digital, keypad entered; calibration stored in nonvolatile memory					
Tare		Push button, 100% of full scale capacity					
Annunciators		Center of zero, motion, net, low battery, over capacity					
Buttons		ON/ZERO, NET, TARE, GROSS, OFF					
Load Cell		Cardinal Scale model CMBC constant moment beam cell					
Sample Rate		1 - 12 samples per second, selectable					
Auto Shut-off		Power saving mode selectable from 1 to 9 minutes					
NTEP Approval		03-030 Accuracy Class III (applies to all HSDC models except HSDC-500)					

Cardinal Scale reserves the right to improve, enhance or modify features and specifications without prior notice. All registered trademarks are the property of their respective owners.

 **Cardinal**[®]
Cardinal Scale Manufacturing Co.
203 E. Daugherty, Webb City, MO 64870 USA
Ph: 417-673-4631 or 800-441-4237 • Fax: 417-673-5001
www.CardinalScale.com

Mobile: m.cardinalscale.com

SOLD BY: